





TECHNICAL REQUIREMENT

1.UNLESS OTHERWISE SPECIFIED CASTING R1-R2.

2.NO MARKING THE TOLERANCE CLASS OF CASTING SIZE CT8,IMPLEMENTATION STANDARD GB/T6414-1999.
NO MARKING THE TOLERANCE CLASS OF PROCESSING SIZE c,IMPLEMENTATION STANDARD GB/T1804-2000.

3.CASTING SURFACE IS FREE FROM CRACK,DEPRESSION AND OTHER DEFECTIONS.

4.CASTING SURFACE SHOULD BE CLEAN AND SMOOTH.

5.ALL THE MARKS SHOULD BE CLEAR ENOUGH TO RECOGNIZE.

6.CASTING SURFACE SMOOTH CONDITION: 50

7.THE PRODUCT APPEARANCE ADOPTS TECHNICS OF UNATTACKALTE ELECTROSTATIC PAINTING
AND THE COATING IS EPOXY WITH GOOD ADHESION.

8.THE COATING THICKNESS:0.1-0.2MM

9.DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.

				DRAWING	王英君	CAP		**Hydrotech**					
				DESIGN	李大泉								
				FIRST CHECK	王振峰								
				SECOND CHECK	周士国	SPECIFICATION	TYPE	MATERIAL	PRESSURE	QTY	N.W	SCALE	PAGE
NO.	MARK	CORRECTION RECORD	SIGNATURE/DATE	APPROVAL	陈仁平	4"X1"	XGQT23	GB/T1348-2009 QT450-10	2.5MPa	1	0.94kg	FULL ALL	6

DRAWING NO.	23-114X33
VERSION NUMBER	A